



Truck Mounted Log Loaders
Designed And Built In Canada!



Model 1034B

Maximum rated lifting capacity @ 10 foot radius: 34,000 lbs.

- This model has been developed for Super B Train applications.
- Boom Reach: 25 feet

<u>Cylinders</u>	<u>Bore / Rod</u>
Boom	8" X 4"
Jib	7" X 3.5"
Stabilizers	6" X 3"

- Normal Operating Pressure: 2,750 psi
- Main Boom, Jib Boom and Cylinder Pins: 2.5" Diam.
"Super Impacto" case hardened to Rc50
(Tough core, hard surface)
- Turntable Bearing: 39"
- Reservoir Capacity: 112 (US Gal.)
- Hydraulic Pump Rated Flow & Pressure
@ 1200 RPM: 107 gmp @ 3000 psi

Vanguard Cranes Inc.

9366 Smiley Road
Chemainus, B.C. Canada V0R 1K4
Phone: 250-416-0212 Fax: 250-416-0232
Email: parts@profabmanufacturing.net
Web: www.vanguardcranes.com



**Truck Mounted Log Loaders
Designed And Built In Canada!**



**Model
1034B**

Available Options (* = recommended)	
Chelsea 440 PTO	* Chelsea 880 PTO
Aluminum Alberta Wide Load Clearance Lights	Aluminum Toolbox, Driver Side with Chainsaw Extension
Aluminum Toolbox, Passenger Side	Steel (Sloped Lid) Toolbox, installed behind Picker
Premier Pintle Hook on Tower	Operator Brush Guard
Swinglock Assembly (Single)	Swinglock Assembly (Dual)
* Front Bumper Reinforcement	Telescoping Stabilizer Arms c/w Hydraulic Cylinders & Controls
Float Valves installed on Swing and Main Boom	Single Rail Frame Insertion (if required)
* (1) twin electric fan oil cooler	(1) automatic electronic fan-control for cooler
Extra Lights on Boom (Qty 2)	Continuous Rotation Tower (Including Electric Swivel)
Chrome Cylinder Package	
Grapple Options	
38" 370° Non Continuous Rotation	
44" 370° Non Continuous Rotation	* 44" Continuous Rotation
1/3 Cord Pulp 370° Non Continuous Rotation	44 " Twin Pin 370° Non-Continuous Rotation
1/3 Cord Pulp Continuous Rotation	4 4 " Twin Pin Continuous Rotation

Vanguard Cranes Inc.

9366 Smiley Road

Chemainus, B.C. Canada V0R 1K4

Phone: 250-416-0212 Fax: 250-416-0232

Email: parts@profabmanufacturing.net

Web: www.vanguardcranes.com